

SCOPE :

This specification applies to the Pb Free high current type SMD inductors
for MSCD-52-SERIES


PRODUCT IDENTIFICATION

MSCD - 52 - 820 K

① ② ③ ④

- ① Product Code
- ② Dimensions Code
- ③ Inductance Code
- ④ Tolerance Code

(1) SHAPES AND DIMENSIONS



(2) ELECTRICAL SPECIFICATIONS

SEE TABLE 1

TEST INSTRUMENTS

L : HP 4284A PRECISION LCR METER (or equivalent)

RDC : CHROMA MODEL 16502 MILLIOHMMETER (or equivalent)

(3) CHARACTERISTICS

- (3)-1 Ambient temperature +60°C Max.
- (3)-2 Operate temperature range -40°C ~ +125°C
(Including self temp. rise)
- (3)-3 Storage temperature range -40°C ~ +125°C



MAG.LAYERS

TABLE 1

MAGLAYERS PT/NO.	Inductance L(μH)	Percent Tolerance	Test Frequency	Resistance RDC(Ω)Max.	Rated DC Current		Marking
					IDC1(A)	IDC2(A)	
MSCD-52-R25□	0.25	N	100kHz/0.25V	5.3m	7.50	7.50	R25
MSCD-52-R82□	0.82	M	100kHz/0.25V	12m	5.50	5.50	R82
MSCD-52-1R0□	1.0	M	100kHz/0.25V	30m	4.50	4.50	1R0
MSCD-52-1R4□	1.4	M.N	100kHz/0.25V	40m	4.00	4.00	1R4
MSCD-52-1R8□	1.8	M.N	100kHz/0.25V	50m	3.30	3.30	1R8
MSCD-52-2R2□	2.2	M	100kHz/0.25V	60m	2.94	3.20	2R2
MSCD-52-2R7□	2.7	M.N	100kHz/0.25V	70m	2.50	2.50	2R7
MSCD-52-3R3□	3.3	M	100kHz/0.25V	80m	2.35	2.70	3R3
MSCD-52-3R9□	3.9	M.N	100kHz/0.25V	90m	2.20	2.20	3R9
MSCD-52-4R7□	4.7	M	100kHz/0.25V	0.14	2.00	2.60	4R7
MSCD-52-5R6□	5.6	M.N	100kHz/0.25V	0.15	1.80	1.80	5R6
MSCD-52-6R8□	6.8	M	100kHz/0.25V	0.16	1.70	2.50	6R8
MSCD-52-8R2□	8.2	M.N	100kHz/0.25V	0.17	1.40	1.40	8R2
MSCD-52-100□	100	M.N	100kHz/0.25V	0.18	1.20	1.20	100
MSCD-52-120□	120	M.N	100kHz/0.25V	0.20	1.18	1.18	120
MSCD-52-150□	150	M.N	100kHz/0.25V	0.22	1.15	1.15	150
MSCD-52-180□	180	M.N	100kHz/0.25V	0.25	1.10	1.10	180
MSCD-52-220□	220	M.N	100kHz/0.25V	0.35	1.00	1.00	220
MSCD-52-270□	270	M.N	100kHz/0.25V	0.45	0.86	0.86	270
MSCD-52-330□	33	K,M	100kHz/0.25V	0.50	0.79	1.05	330
MSCD-52-390□	39	K,M	100kHz/0.25V	0.69	0.75	1.00	390
MSCD-52-470□	47	K,M	100kHz/0.25V	0.72	0.73	0.88	470
MSCD-52-560□	56	K,M	100kHz/0.25V	0.84	0.55	0.78	560
MSCD-52-680□	68	K,M.N	100kHz/0.25V	0.90	0.52	0.52	680
MSCD-52-820□	82	K,M	100kHz/0.25V	0.95	0.50	0.70	820
MSCD-52-101□	100	K,M	100kHz/0.25V	1.30	0.40	0.40	101
MSCD-52-121□	120	K,M	100kHz/0.25V	1.38	0.36	0.36	121
MSCD-52-151□	150	K,M	100kHz/0.25V	1.81	0.30	0.30	151
MSCD-52-181□	181	K,M	100kHz/0.25V	1.95	0.26	0.26	181
MSCD-52-221□	220	K,M	100kHz/0.25V	2.10	0.25	0.25	221
MSCD-52-271□	270	K,M	100kHz/0.25V	2.42	0.21	0.21	271
MSCD-52-331□	330	K,M	100kHz/0.25V	3.82	0.18	0.18	331
MSCD-52-391□	390	K,M	100kHz/0.25V	4.68	0.16	0.16	391
MSCD-52-471□	470	K,M	100kHz/0.25V	5.10	0.15	0.15	471
MSCD-52-561□	560	K,M	100kHz/0.25V	6.00	0.14	0.14	561
MSCD-52-681□	680	K,M	100kHz/0.25V	7.60	0.13	0.13	681
MSCD-52-821□	820	K,M	100kHz/0.25V	9.12	0.07	0.07	821
MSCD-52-102□	1000	K,M	100kHz/0.25V	9.87	0.05	0.05	102

※ □ Specify the inductance tolerance, K(±10%),M(±20%),N(±30%)


※ IDC1 : Based on inductance change ($\Delta L/L_0$: drop 10% Max.) @ ambient temp. 25°CIDC2 : Based on temperature rise (ΔT : 40°C TYP.)

Rated DC Current : The less value which is IDC1 or IDC2.

**MAG.LAYERS**


(4) RELIABILITY TEST METHOD

MECHANICAL

TEST ITEM	SPECIFICATION	TEST DETAILS
Substrate bending	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage or electrical damage.	<p>The sample shall be soldered onto the printed circuit board in figure 1 and a load applied until the figure in the arrow direction is made approximately 3mm.(keep time 30 seconds)</p> <p>PCB dimension shall the page 7/9</p> <p style="text-align: center;">F(Pressurization)</p>  <p style="text-align: center;">PRESSURE ROD figure-1</p>
Vibration	$\Delta L/L_0 \leq \pm 5\%$ There shall be no mechanical damage.	<p>The sample shall be soldered onto the printed circuit board and when a vibration having an amplitude of 1.52mm and a frequency of from 10 to 55Hz/1 minute repeated should be applied to the 3 directions (X,Y,Z) for 2 hours each.</p> <p>(A total of 6 hours)</p>
Solderability	New solder More than 90%	<p>Flux (rosin, isopropyl alcohol{JIS-K-1522}) shall be coated over the whole of the sample before hard, the sample shall then be preheated for about 2 minutes in a temperature of 130~150°C and after it has been immersed to a depth 0.5mm below for 3±0.2 seconds fully in molten solder M705 with a temperature of 245±5°C.</p> <p>More than 90% of the electrode sections shall be covered with new solder smoothly when the sample is taken out of the solder bath.</p>



MECHANICAL

TEST ITEM	SPECIFICATION	
Resistance to Soldering heat (reflow soldering)	<p>There shall be no damage or problems.</p>  <p>The graph shows Soldering temperature (°C) on the y-axis (0 to 300) and time on the x-axis. The Pre-heating phase is from 0 to 150°C over 2 minutes, reaching a plateau between 150-180°C. The soldering phase starts at 150°C, peaks at 260±3°C for 10 seconds, and then drops to 230°C over 30 seconds. The Slow cooling phase follows, stored at room temperature for 2 minutes or more.</p> <p>Temperature profile of reflow soldering</p> <p>Pre-heating 150 ~ 180°C 2 min</p> <p>soldering (Peak temperature 260±3°C 10 sec) 30 sec Min (230°C)</p> <p>Slow cooling (Stored at room temperature) 2 min. or more</p>	<p>Temperature profile of reflow soldering</p> <p>Pre-heating 150 ~ 180°C 2 min</p> <p>soldering (Peak temperature 260±3°C 10 sec) 30 sec Min (230°C)</p> <p>Slow cooling (Stored at room temperature) 2 min. or more</p> <p>The specimen shall be passed through the reflow oven with the condition shown in the above profile for 1 time. The specimen shall be stored at standard atmospheric conditions for 1 hour, after which the measurement shall be made.</p>

ELECTRICAL

TEST ITEM	SPECIFICATION	TEST DETAILS
Insulation resistance	<p>There shall be no other damage or problems.</p>	<p>DC 100V voltage shall be applied across this sample of top surface and the terminal.</p> <p>The insulation resistance shall be more than $1 \times 10^8 \Omega$.</p>
Dielectric withstand voltage	<p>There shall be no other damage or problems.</p>	<p>AC 100V voltage shall be applied for 1 minute across the top surface and the terminal of this sample</p>
Temperature characteristics	<p>$\Delta L/L20^\circ\text{C} \leq \pm 10\%$</p> <p>0~2000 ppm/°C</p>	<p>The test shall be performed after the sample has stabilized in an ambient temperature of -20 to +85°C, and the value calculated based on the value applicable in a normal temperature and normal humidity shall be $\Delta L/L20^\circ\text{C} \leq \pm 10\%$.</p>



MAG.LAYERS

ENVIRONMENT CHARACTERISTICS

TEST ITEM	SPECIFICATION																
High temperature storage	$\Delta L/Lo \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96±4 hours in an atmosphere with a temperature of 85±2°C and a normal humidity. Upon completion of the measurement shall be made after the sample has been left in a normal temperature and normal humidity for 1 hour.															
Low temperature storage	$\Delta L/Lo \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96±4 hours in an atmosphere with a temperature of -25±3°C. Upon completion of the test, the measurement shall be made after the sample has been left in a normal temperature and normal humidity for 1 hour.															
Change of temperature	$\Delta L/Lo \leq \pm 5\%$ There shall be no other damage or problems	The sample shall be subject to 5 continuous cycles, such as shown in the table 2 below and then it shall be subjected to standard atmospheric conditions for 1 hour, after which measurement shall be made.															
		table 2															
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Temperature</th> <th>Duration</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-25±3°C (Thermostat No.1)</td> <td>30 min.</td> </tr> <tr> <td>2</td> <td>Standard atmospheric</td> <td>No.1→No.2</td> </tr> <tr> <td>3</td> <td>85±2°C (Thermostat No.2)</td> <td>30 min.</td> </tr> <tr> <td>4</td> <td>Standard atmospheric</td> <td>No.2→No.1</td> </tr> </tbody> </table>		Temperature	Duration	1	-25±3°C (Thermostat No.1)	30 min.	2	Standard atmospheric	No.1→No.2	3	85±2°C (Thermostat No.2)	30 min.	4	Standard atmospheric	No.2→No.1
	Temperature	Duration															
1	-25±3°C (Thermostat No.1)	30 min.															
2	Standard atmospheric	No.1→No.2															
3	85±2°C (Thermostat No.2)	30 min.															
4	Standard atmospheric	No.2→No.1															
Moisture storage	$\Delta L/Lo \leq \pm 5\%$ There shall be no mechanical damage.	The sample shall be left for 96±4 hours in a temperature of 40±2°C and a humidity(RH) of 90~95%. Upon completion of the test, the measurement shall be made after the sample has been left in a normal temperature and normal humidity more than 1 hour.															
Test conditions : The sample shall be reflow soldered onto the printed circuit board in every test.																	



MAG.LAYERS


(5) LAND DIMENSION (Ref.)

PCB: GLASS EPOXY $t=1.6\text{mm}$


(5)-1 LAND PATTERN DIMENSIONS

(STANDARD PATTERN)

Unit:mm




(5)-2 SUBSTRATE BENDING TEST BENDING TEST BOARD




MAG.LAYERS

(6) PACKAGING

(6)-1 CARRIER TAPE DIMENSIONS (mm)



(6)-2 TAPING DIMENSIONS (mm)





MAG.LAYERS

MSCD-52-SERIES

Page-7/8

(6)-3 REEL DIMENSIONS (mm)



(6)-4 QUANTITY

2500 pcs/Reel

The products are packaged so that no damage will be sustained.



MAG.LAYERS

MSCD-52-SERIES

Page-8/8